

# 8GM

## Smart Controller

### **butech**

PORCELANOSA Grupo

By **Warmup**

The 8GM is designed to look great in both modern and traditionally styled homes, with glass effect front faces and bevelled chrome edges to reflect wall colours.

The large colour touchscreen can be customised with different themes and uploadable photo backgrounds. There's even a 7 day local weather forecast, and traffic alerts built in.

The 8GM can control your heating automatically and reduces your heating usage by up to 25%. It works by using the location services built into smartphones, as well as learning your routines and the most efficient settings for your home.

So your heating is always at the right temperature, effortlessly. Your home is automatically warm as you arrive, and running efficiently when you're away. Just like magic.



#### **BUTECH BUILDING TECHNOLOGY**

CV-20 KM 2,5, 12540, Vila-real, Castellón, SPAIN

Tel: (+34) 964 536 200

Fax: (+34) 964 530 034

UK: [ufhhelpline.uk@butech.es](mailto:ufhhelpline.uk@butech.es)

IRE: [ufhhelpline.ie@butech.es](mailto:ufhhelpline.ie@butech.es)

# **butech**

PORCELANOSA Grupo

By **Warmup**

# Features

- The 8GM can be controlled using the “MyUFH by butech” App via your smartpone or tablet, available on iOS and Android or through the my.butech.net web portal with any desktop or mobile web browser.
- The 8GM can control your heating automatically and reduces your heating usage by up to 25% by using the location services built into smartphones.
- Natural Language Programming, programming that speaks your language. If you don't want to use SmartGeo or just want to make a quick adjustment, Natural Language Programming is simple to use.
- BEAB Approved and CE marked meeting the highest safety standards for ultimate peace of mind.



- 3yr Warranty.



# Technical Data

## 8GM - TECHNICAL SPECIFICATIONS

MODEL	BU-SC-NG-01
CODE	100232083
INPUT VOLTAGE	230V +/- 15% at 50Hz
MAX LOAD	16A (3680W)
DIMENSIONS	(H/W/D): 90 x 120 x 18mm (from wall)
SENSORS	AIR & FLOOR (AMBIENT)
SENSOR TYPE	NTC10K 3m LONG (CAN BE EXTENDED TO 50m)
IP RATING	IP33
OPERATING FREQUENCY	2401-2483MHz
MAX. RADIO-FREQUENCY POWER TRANSMITTED	18 dBm
INSTALLATION DEPTH	35mm BACK BOX
DISPLAY SIZE	3.5" FULL COLOUR TOUCHSCREEN
COMPATIBILITY	IDEAL FOR ELECTRIC & HYDRONIC UNDERFLOOR HEATING UP TO 16A. COMBI & SYSTEM BOILERS WITH SWITCH LIVE (230 V AC) INPUT
Er-P CLASS	IV